# WorkForce Pro WF-C878RD3TWFC (MEA)

### Cut your downtime, save cost and improve sustainability with this ultra-reliable business inkjet MFP

Reduce energy use and downtime, while still maintaining high productivity with Epson's WorkForce Pro RIPS WF-C878R. Thanks to this ultra-reliable business inkjet multifunction printer, users can print up to 20,000 pages without needing to change supplies.<sup>1</sup>

### High yield printing

This low-intervention MFP prints up to 20,000 pages in mono or colour without changing the ink supplies.<sup>1</sup> This means there is low user intervention, increasing productivity.

### Precision Core Heat-free technology

Epson Heat-Free Technology requires no heat to warm up when it is switched on or woken from sleep, which significantly reduces energy consumption and therefore saves money. This also means Epson's Heat-Free inkjets can deliver a fast first page out time (FPOT) of 5.5 seconds compared to laser printers, which need to preheat the fuser to print.

### Enhance functionality with in-house (EDA, EPA) and third party solutions (Open Platform)

Gain complete control of printing operations with Epson and its partners solutions, allowing devices to be set up to meet specific and changing business requirements.

### **Epson Remote Services (ERS)**

Our cloud-based device monitoring and management system helps service providers to perform accurate remote diagnosis without compromising on security. The embedded agent on the WF-C878R allows for seamless setup and use.

### DATASHEET / BROCHURE



### **KEY FEATURES**

- High reliability With few moving parts, and low intervention, increase printer uptime
- High print yield Print up to 20,000 pages without changing the supplies<sup>1</sup>
- Low power consumption Epson's Heat-Free technology uses no heat, reducing energy consumption
- Epson Remote Services Cloud-based, advanced diagnosis of Epson printers and MFPs.



### PRODUCT SPECIFICATIONS

TECHNOLOGY		
Printing Method	PrecisionCore™ Print Head	
Nozzle Configuration	800 Nozzles Black, 800 Nozzles per Color	
Minimum Droplet Size 4.6 pl, With Variable-Sized Droplet Technology   Ink Technology Replaceable Ink Pack System (RIPS)		
		Category
All-in-One Functions	Print, Scan, Copy, Fax	
PRINT		
First Page Out	Monochrome 5.5 Seconds, Colour 5.5 Seconds	
rinting Speed ISO/IEC 24734 25 pages/min Monochrome, 24 pages/min Colour		
Duplex Printing Speed	17 A4 Pages/min Monochrome, 16 A4 Pages/min Colour	
ISO/IEC 24734		
Maximum Printing Speed	35 pages/min Colour (plain paper 75 g/m <sup>2</sup> ), 35 pages/min Monochrome (plain paper 75 g/m <sup>2</sup>	
Printing Resolution	4,800 x 1,200 DPI	
Printing Volume	75,000 pages per month	
	The maximum number of printed pages per month based on the performance capabilities of	
	the printer, including ISO rated print speeds and paper handling capabilities.	
Colours	Black, Cyan, Yellow, Magenta	
For detailed information on p	rinting speeds please visit http://www.epson.eu/testing.	
SCAN		
Double-sided scanning	Yes	
Single-sided scan speed (A4	25 ipm with ADF scan 200 dpi (flatbed) 4 sec. with flatbed scan	
black)	,	
Doubled-sided scan speed	200 dpi (with ADF); , 45 ipm with ADF scan	
(A4 black)		
Single-sided scan speed (A4	200 dpi (with ADF); , 25 ipm with ADF scan 200 dpi (flatbed) 4 sec. with flatbed scan	
colour)		
Doubled-sided scan speed	200 dpi (with ADF); , 45 ipm with ADF scan	
(A4 colour)		
Optical Resolution	600 DPI x 600 DPI (Horizontal x Vertical)	
Optical Resolution (ADF)	600 DPI x 600 DPI (Horizontal x Vertical)	
Output formats	JPEG, TIFF, PDF	
Scanner type	Contact image sensor (CIS)	
FAX	Walk up black and white and colour for conshility	
Type of fax	Walk-up black and white and colour fax capability	
Fax Transmission Speed	Up to 33.6kbps / Approx. 3 sec/page	
	CCITU/ITU Group3 fax with Error Correction Mode	
Error correction mode	-	
Fax speed dials (max)	2,000 names and numbers	
Fax speed dials (max) Page memory	2,000 names and numbers Up to 550 pages/ 6MB (ITU-T No. 1 chart)	
Fax speed dials (max)	2,000 names and numbers	

### WorkForce Pro WF-C878RD3TWFC (MEA)

### WHAT'S IN THE BOX

- Quick Setup Guide
- Main unit
- Warranty Documents
- User manual (CD)
- Power cable
- Paper tray
- Initialization Ink Supply Units



### PRODUCT SPECIFICATIONS

CONNECTIVITY	
Network Printing Protocols	LPR, FTP, IPP, Port 9100, TCP/IPv4, TCP/IPv6, IPSec, SMB 2.0
Network Management	SNMP, HTTP, DHCP, IPSec, IEEE 802.1X, SNMP 3.0
Protocols	
Network Protocol	HTTPS, IPv4, IPv6, SNMP
Network Scanning Protocols	Bonjour/Airprint, FTP, SMB 2.0, SMB 3.0
Interfaces	Hi-Speed USB - compatible with USB 2.0 specification, Ethernet Interface (1000 Base-T/ 100-
	Base TX/ 10-Base-T), USB host, Wi-Fi Direct, USB 2.0 Type A (2x), Wireless LAN IEEE
	802.11a/b/g/n, USB 3.0 Type B
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA2 PSK (AES), WPA2 Enterprise (AES)
Network Protocol	TCP/IPv4, TCP/IPv6, TCP, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL/TLS
PAPER / MEDIA HANDLING	
Paper Formats	A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B5 (17.6x25.7 cm), C4 (Envelope), C6
	(Envelope), No. 10 (Envelope), Letter, 10 x 15 cm, 13 x 18 cm, 20 x 25 cm, Legal, A3 (29.7x42.0
	cm), B4 (25.7x36.4 cm), B6 (12.5x17.6 cm), C5 (Envelope), DL (Envelope), HLT, EXE, Tabloid,
	A3+
Automatic Document Feed	50 pages
Compatible Paper Weight	64 g/m² - 300 g/m²
Duplex	Yes
Output Tray Capacity	250 Sheets
Paper Tray Capacity	835 Sheets Standard, 1,835 Sheets Maximum
Rear paper path (special	Yes
media)	
Number of paper trays	4
PAPER FEED RASF	
Paper Input Name	RASF
Paper Formats	A3+, A3, A4, C4 (Envelope), Letter, User defined
Compatible paper weight	64 g/m² - 300 g/m²
PAPER FEED C1	
Paper Input Name	C1
Compatible paper weight	64 g/m² - 200 g/m²
Paper Capacity 1	250 Sheets of Plain Paper, 80gsm
{SPECGROUPNAMEPAPERF	·EEDC2-C4}
Paper Input Name	C2-C4
Paper Formats	A3, A4, A5, Letter, User defined
Compatible paper weight	64 g/m² - 200 g/m²
Paper Capacity 1	500

### WorkForce Pro WF-C878RD3TWFC (MEA)



### PRODUCT SPECIFICATIONS

## WorkForce Pro WF-C878RD3TWFC (MEA)

GENERAL		
Energy Use	40 Watt (standalone copying, ISO/IEC 24712 pattern), TEC 0.22 kWh/week	
Supply Voltage	AC 220 V - 240 V	
Product dimensions	621 x 652 x 1,107 mm (Width x Depth x Height)	
Compatible Operating	Citrix XenApp 7.x, Linux, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Ma	
Systems	OS 10.8.x, Mac OS 10.9.x, Microsoft Windows XP (Home Edition / Prof / Prof X64 / Vista), SAP, Windows 10, Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 (32/64bit), Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Server 2016, Windows Vista, Windows Vista (32/64 bit), Windows Vista x64, Windows XP x64, Windows Server 2003 R2	
Sound Power	Operation: 6.6 B (A)	
Noise	Operation: 51 dB (A)	
Mobile and Cloud printing	Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint,	
services	Google Cloud Print	
Power supply	100V, 110V, 220V, 240V	
ADDITIONAL FEATURES		
Features	Touchscreen, Direct scan-to-print without PC, Direct print from USB	
Panel	Type: Color, Touchscreen, Diagonal: 12.7 cm	
Media Handling	Automatic duplex (A4/A3, plain paper), Portrait & Landscape printing, Rear specialty media	
	feed, Thick Media Support	
OTHER FEATURES		
Emulations	PCL6, PCL5c, PCL5e, ESC/P-R, PDF 1.7, PostScript 3	



#### **SUPPLIES**

- WorkForce Pro WF-C87xR Black XL Ink Supply Unit
- WorkForce Pro WF-C87xR Cyan XL Ink Supply Unit
- WorkForce Pro WF-C87xR Magenta XL Ink Supply Unit
- WorkForce Pro WF-C87xR Yellow XL Ink Supply Unit
- Maintenance box
- Standard Cassette Maintenance Roller
- Optional Cassette Maintenance Roller

#### **OPTIONAL ACCESSORIES**

- 500-Sheet Paper Cassette C12C932611
- WF-C878R/WF-C879R Printer Stand C12C934321
- Card Reader Holder
- C12C932921
- Retractable output tray C12C934171

#### LOGISTICS INFORMATION

SKU	C11CH60402BP C11CH60402BZ
EAN code	8715946675930
Country of Origin	Indonesia



\* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

laly 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway 1. 1Approx. page yield with the WF-C878R. Actual yield +47 67 11 37 00

will vary depending on images printed and usage conditions. For more information visit Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 465-9621 www.epson.eu/pageyield. Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min)

Switzerland 022 592 7923

Turkey (0212) 3360303 United Kingdom 0871 222 6702

### WorkForce Pro WF-C878RD3TWFC (MEA)

C13T05A100 20,000 pages

C13T05A300 20,000 pages

C13T05A400 20,000 pages

pages

pages

200,000

C13S210048 200.000

20,000 pages

C13T05A200

C13T671400

C13S210049

**EPSON** 

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice. Last extracted: 2020-07-21